

# Reducing Silica Exposure During Lateral Drilling of Concrete


**Michael R. Cooper, The Lippy Group, LLC; Pam Susi, CPWR – The Center for Construction Research and Training; David Rempel, Division of Occupational and Environmental Medicine, Department of Medicine, University of California at San Francisco**

**Problem:**

- Silica is found in numerous building materials including concrete and is a pervasive exposure risk in construction.
- Exposures associated with use of rock drills for lateral drilling in concrete structures have not been characterized or controlled.

**Resolution:**

- The University of California at San Francisco is developing a jig to support a rock drill and reduce the upper body strain to workers when drilling.
- A dust control system was used with the jig to evaluate its impact on silica exposure using a randomized study design.
- The study included trials of the following drilling conditions:
  1. drilling with jig and vacuum (n=4);
  2. drilling with jig and without vacuum (n=4); and
  3. manual drilling, without jig and without vacuum (n=4)
- The dust collection system consisted of a vacuum (114 cfm air flow rate), a drill bit shroud and a 2-inch diameter hose.



Manual Drilling

14 times the NIOSH REL




Drilling with the jig, no vacuum

6 times the NIOSH REL



Drill bit shroud and vacuum hose



Drilling with the jig and vacuum

80% of the NIOSH REL

**Results:**

- Drilling without the jig and dust control resulted in mean exposure to respirable silica 14 times the NIOSH REL.
- Drilling with the jig reduced silica exposure 55% compared to drilling without the jig.
- Drilling while using the jig and the vacuum reduced exposures by 94% compared to manual drilling and brought the mean exposure to 80% of the REL.

**Lessons learned:**


- Lateral concrete drilling is likely to generate hazardous airborne silica concentrations.
- Use of the jig without the vacuum system reduced respirable silica exposure by approximately half, but exposures still exceeded the REL.
- Use of the tested vacuum dust collection system reduced the operator’s exposure to 80% of the NIOSH REL for respirable silica based on task TWAs.
- **Combined use of the jig and vacuum system is recommended to reduce both musculoskeletal strain and silica exposure.**

**References:**

1. Borm, P.J.A. and D. Donaldson: The quartz hazard in the construction industry. *Indoor and Built Environ.* 8:107-112 (1999).
2. National Institute for Occupational Safety and Health (NIOSH): NIOSH hazard review: health effects of occupational exposure to respirable crystalline silica. DHHS/NIOSH Publication No. 2002-129. Cincinnati: NIOSH; 2002.
3. Rappaport, M. S., M. Goldberg, P. Susi and R. F. Herrick: Excessive exposure to silica in the US construction industry. *Ann. Occup. Hyg.* 47(2): 111-122 (2003).
4. Flynn, M. R. and P. Susi: Engineering controls for selected silica and dust exposures in the construction industry A Review. *Appl. Occup. Environ. Hyg.* Vol. 18 (4): 268-277 (2003).
5. Flanagan, M.E.: "Green River Bridge Project Silica Exposure Assessment." [Online] Available at [http://depts.washington.edu/cnstsaf/bridge\\_silica.pdf](http://depts.washington.edu/cnstsaf/bridge_silica.pdf) (Accessed December 8, 2009).
6. Flanagan, M.E., N. Seixas, P. Becker, B. Takacs, and J. Camp: Silica exposure on construction sites: Results of an exposure monitoring data compilation project. *J. Occup. Environ. Hyg.* 3:144–152 (2006).
7. Bureau of Labor Statistics, U.S. Department of Labor, *Career Guide to Industries, 2010-11 Edition*, Construction, on the Internet at <http://www.bls.gov/oco/cg/cgs003.htm> (Accessed July 28, 2011).

**Acknowledgements:**

Jerome Williams for arranging use of their training center and identifying a skilled operator to run the tested equipment. The operator of the equipment whose patience, attentiveness and hard work provided us with the data described in this paper. Margaret Robbins and Alan Barr for their assistance in data collection. This research was funded by CPWR – The Center for Construction Research and Training (CPWR) through cooperative agreement OH008307 from the National Institute of Occupational Safety and Health (NIOSH). Its contents are solely the responsibility of the authors and do not necessarily represent the official views of CPWR or NIOSH.



Respirable Silica During Concrete Drilling with a Pneumatic Rock Drill

	Mean, mg/m <sup>3</sup> (range)	Standard Deviation	Percent Reduction <sup>A</sup>
Drilling with jig and vacuum	0.04 (<0.02 - 0.05)	0.01	94.3
Drilling with jig and without vacuum	0.30 (0.09 – 0.64)	0.24	55.3
Manual drilling	0.68 (0.42 – 0.84)	0.19	NA

<sup>A</sup> compared to manual drilling, without the jig and vacuum

